

# Kashmir White

India



MEKANISKE STENHUGGERI A/S  
GRUNDLAGT 1797

DS: EN 12058	Internal Flooring of Natural Stone	Date of Test: 2019
DS: EN 1341	External Paving of Natural Stone	Date of Test: N/A
DS: EN 1469	External Cladding of Natural Stone	Date of Test: N/A

### General for all use:

Dimensions and dimensional variation	Complies
Nominal thickness an variation	Complies
Release of dangerous substances	None in conditions of use as Internal-/External Flooring, External Paving or Cladding
Fire performance	Deemed to satisfy
Reaction to fire Class A1	Deemed to satisfy

### Internal Flooring and Stairs:

Water absorption acc. to DS: EN 13755	0,41%		
Bending/Flexural strength acc. to DS: EN 12372	9,20 Mpa		
Density acc. to DS: EN 1936	2698 kg/m <sup>3</sup>		
Compression Strength acc. to DS: EN 1926	166 Mpa		
Petrografic evaluation acc. to DS: EN 12407	Gneis		
Mineralogical composition (by weight)	Plagioklas > 50%, kvarts > 20%, biotit 10%, Feltspar > 10%, other < 10 %		
Slip resistance in dry	N/A	Slip resistance in wet	N/A

### External Flooring, Cladding and Stairs:

Porosity DS: EN 1936	N/A
Density DS: EN 1936	2698 kg/m <sup>3</sup>
Water absorption DS: EN 13755	0,41%
Bending strength DS: EN 12372	9,20 Mpa
Determination of frost resistance DS: EN 12371	N/A
Compressive strength DS: EN 1926	166 Mpa
Breaking load at dowl hole DS: EN 13364	N/A
Determination of ageing by Thermal shock	N/A
Determination of resistance to salt crystalization DS: EN 12370	N/A